

MATERIAL SAFETY DATA SHEET



GRANITE CONSTRUCTION INCORPORATED
P. O. BOX 50085, WATSONVILLE, CA 95077-5085
831-724-1011

PREPARED: 10-16-07
REPLACES: 09-19-02

SECTION I MATERIAL IDENTIFICATION

CHEMICAL NAME Not Applicable	CHEMICAL FORMULA Mixture	MOLECULAR WEIGHT Not Applicable
TRADE NAME(S) Construction Sand		
SYNONYMS Crushed Stone, Fine	DOT IDENTIFICATION NO. None	

SECTION II PRODUCT AND COMPONENT DATA

COMPONENT(S) CHEMICAL NAME	CAS REGISTRY NO.	% (APPROX.) (optional)	OSHA PEL	ACGIH TLV
Mineral Aggregates (sand)	Mixture	100	See Section X	See Section X
Silica, crystalline – typically Quartz (content typically greater than 1% and can be higher than 20%)	14808-60-7	Varies	See Section X	See Section X
Other possible forms of crystalline silica				
Cristobalite	14464-46-1	Varies	See Section X	See Section X
Tridymite	15468-32-3	Varies	See Section X	See Section X

SECTION III PHYSICAL DATA

APPEARANCE AND ODOR Angular particles, light/salt and pepper colored, ranging in size from grains to small pebbles. No odor.	SOLUBILITY IN WATER Negligible		
BOILING POINT	NA	SPECIFIC GRAVITY (H₂O = 1 @ 39.2 F)	2.4 – 2.8
VAPOR PRESSURE (mm Hg)	NA	MELTING POINT	NE
VAPOR DENSITY IN AIR (AIR = 1)	NA	EVAPORATION RATE (Butyl Acetate = 1)	NA

SECTION IV PHYSICAL HAZARDS (FIRE AND EXPLOSION HAZARD DATA)

FLASHPOINT (METHOD USED) Not flammable or combustible	FLAMMABLE LIMITS IN AIR (% Vol. in air) Not flammable or combustible	LEL NA	UEL NA
---	--	------------------	------------------

EXTINGUISHING AGENTS
None required

UNUSUAL FIRE AND EXPLOSION HAZARDS

Contact with powerful oxidizing agents may cause fire and/or explosion.

SECTION V REACTIVITY DATA

STABILITY	Unstable		CONDITIONS TO AVOID Avoid contact with incompatible materials.
	Stable	X	

INCOMPATIBILITY (MATERIALS TO AVOID)

Silica reacts violently with powerful oxidizing agents such as fluorine, boron trifluoride, chlorine trifluoride, manganese trifluoride, oxygen difluoride and hydrogen peroxide yielding possible fire and/or explosions. Silica is also incompatible with acetylene and ammonia. Silica dissolves readily in hydrofluoric acid producing a corrosive gas – silicon tetrafluoride.

HAZARDOUS DECOMPOSITION PRODUCTS

Silica-containing respirable dust particles may be generated if hardened product is subjected to mechanical forces such as in demolition work and surface modification (sanding, grooving, chiseling, etc.)

HAZARDOUS POLYMERIZATION	May Occur		CONDITIONS TO AVOID Not Applicable
	Will Not Occur	X	

SECTION VI TOXICITY AND FIRST AID

PRIMARY ROUTE(S) OF EXPOSURE	Inhalation? Yes	Skin? Yes	Ingestion? No
-------------------------------------	-----------------	-----------	---------------

HEALTH HAZARDS (ACUTE AND CHRONIC)

Eye Contact: Contact with dust may be irritating.

Skin Contact: Contact with dust may be irritating.

Skin Absorption: Not applicable.

Ingestion: Ingestion of large amounts may cause gastrointestinal irritation and/or blockage.

Inhalation: Dusts may irritate the nose, throat, and respiratory tract. Avoid breathing excessive dust.

Repeated and prolonged (chronic) exposure to respirable dust in excess of allowable exposure limits can result in pneumoconiosis, a lung disease.

Repeated and prolonged (chronic) exposure to respirable crystalline silica-containing dust in excess of allowable exposure limits may cause silicosis, a progressive pneumoconiosis, and possibly lung cancer. Smoking may further increase the risk of lung disease. Dry product or hardened product subjected to mechanical forces (such as in demolition work) may result in exposure to respirable dust.

CARCINOGENICITY

Crystalline silica, a component of this product, is listed by IARC as a carcinogen. The IARC has determined that there is sufficient evidence of carcinogenicity in experimental animals exposed to crystalline silica and limited evidence of its carcinogenicity in humans. The NTP has listed respirable crystalline silica as a known human carcinogen. The American Conference of Governmental Industrial Hygienists (ACGIH) has listed respirable crystalline silica (quartz) as a suspected human carcinogen (A-2 designation).

NTP

Silica –
Known
Carcinogen

IARC

Silica -
Carcinogen
(Group 1)

OSHA

NE

CALIFORNIA PROPOSITION 65 WARNING

"This product contains a chemical known to the State of California to cause cancer."

CA LISTED CARCINOGEN(S)

Crystalline silica (quartz, cristobalite)

SIGNS AND SYMPTOMS OF EXPOSURE

The signs and symptoms of acute exposure to dust may include irritation of the eyes, skin and respiratory tract

Symptoms of silicosis include (but may not be limited to): Shortness of breath, difficulty breathing with or without exertion, coughing, diminished work capacity, diminished chest expansion, reduction in lung volume, right heart enlargement or failure.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE

Contact with dust may aggravate existing skin and/or eye conditions. Inhaling respirable dust may aggravate existing respiratory conditions.

EMERGENCY AND FIRST AID

Eyes: Immediately flush eye(s) with plenty of clean water for at least 15 minutes, while holding the eyelids(s) open. Occasionally lift the eyelid(s) to ensure thorough rinsing. Seek medical attention at once and continue to flush eye(s) until a physician takes charge.

Skin: Flush skin with clean water for at least 15 minutes. Remove and wash contaminated clothing. Contact a physician if irritation persists or later develops. Burns should be treated as caustic burns.

Ingestion: If conscious, give large quantity of water to dilute the stomach contents. Do not attempt to make the person vomit unless directed by medical personnel. Contact a physician immediately.

Dust inhalation: Remove to fresh air. Dust in throat and nasal passages should clear spontaneously. Contact physician if irritation persists or later develops.

SECTION VII PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Personnel involved in cleanup processes should implement controls as identified in Section VIII as appropriate. Prevent spilled materials from entering streams, drainages, or sewers where it can harden and clog flow.

WASTE DISPOSAL METHOD

None of the components in this product are subject to the reporting requirements of Title III SARA, 1986, and 40 CFR 372. Material can be retained until it hardens. Dispose of waste materials only in accordance with applicable federal, state, and local laws and regulations.

STORAGE AND HANDLING PRECAUTIONS

Respirable dust may be generated during processing, handling and storage. The controls identified in Section VIII should be applied as appropriate.

Do not store near food and beverages or smoking material. Avoid incompatible materials.

SECTION VIII PERSONAL PROTECTION AND CONTROL MEASURES

RESPIRATORY PROTECTION

Not required under normal use and working conditions. For air contaminant concentrations which exceed or are likely to exceed applicable exposure limits, use a NIOSH-MSHA approved, contaminant-specific, air-purifying respirator. If such concentrations are sufficiently high that the air-purifying respirator is inadequate, or if oxygen adequate to sustain life is not present, use a positive pressure self-contained breathing apparatus. Consult an industrial hygienist for evaluation of exposures. Follow all applicable MSHA or OSHA respirator use, fitting, and training standards and regulations.

VENTILATION Use only in well ventilated areas. Natural ventilation generally adequate to maintain exposures below appropriate exposure limits under anticipated use conditions.	Local Exhaust As required	Special
	Mechanical (General) As required	Other

PROTECTIVE GLOVES Not required	EYE PROTECTION Safety glasses with side shields should be worn as minimum protection. Dust goggles should be worn when excessively (visible) dusty conditions are present or anticipated.
--	---

OTHER PROTECTIVE CLOTHING OR EQUIPMENT

Not required

HYGIENE

Use work practices which minimize generation of airborne dust. Use normal good hygiene practices. Wash hands with soap and water before eating, drinking, smoking, and using toilet facilities. Wash work clothes after each use.

OTHER CONTROL MEASURES

A fresh water supply for emergency first aid and washing facilities should be readily available. Workers should station themselves on the windward side of dust emissions when possible. Respirable dust levels should be monitored as needed to evaluate exposures during handling and use of product, including activities which generate dust from hardened product. Exposures in excess of the PEL should be reduced to the lowest feasible level through engineering and administrative controls (such as source control, ventilation and/or work practice changes); respiratory protection should be used only where exposures continue to exceed applicable PEL(s).

SECTION IX TRANSPORTATION

DOT HAZARD CLASS None	PLACARD REQUIRED None
---------------------------------	---------------------------------

LABEL REQUIRED

Label as required by the OSHA and MSHA Hazard Communication standards [29 CFR 1910.1200 (f) and 30 CFR Part 42], and applicable state and local regulations.

SECTION X EXPOSURE LIMITS

		MSHA PEL	OSHA PEL	NIOSH REL	ACGIH TLV
PARTICULATES (NOT OTHERWISE REGULATED)	TWA	10 mg/m ³ (total)	15 mg/m ³ (total) 5 mg/m ³ (respirable)	NE	10 mg/m ³ (inhalable) 3 mg/m ³ (respirable)
	STEL	NE	NE	NE	NE
	C	NE	NE	NE	NE
	IDLH	NE	NE	NE	NE
	OTHER EXPOSURES LIMITS: Cal/OSHA PEL – 10 mg/m ³ (total), 5 mg/m ³ (respirable)				
CRYSTALLINE SILICA (QUARTZ, CRISTOBALITE, TRIDYMITE)	TWA	MSHA PEL 30 mg/m ³ / (%SiO ₂ +2) (total particulate containing silica)	OSHA PEL 10 mg/m ³ / (%SiO ₂ +2) (respirable particulate containing silica)	NIOSH REL 0.05 mg/m ³ (respirable silica)	ACGIH TLV 0.025 mg/m ³ (respirable quartz and cristobalite)
	STEL	NE	NE	NE	NE
	C	NE	NE	NE	NE
	IDLH	NE	NE	25 mg/m ³ (respirable cristobalite and/or tridymite) 50 mg/m ³ (respirable quartz)	NE
	OTHER EXPOSURE LIMITS: Cal/OSHA PEL – 0.1 mg/m ³ (respirable quartz), 0.05 mg/m ³ (respirable cristobalite and tridymite)				

NOTES

PEL = permissible exposure limit
 REL = recommended exposure limit
 TLV = threshold limit value
 % SiO₂ = percent silicon dioxide (silica) in dust

TWA = 8-hour time-weighted average
 STEL = short-term exposure limit (15-minute average)
 C = ceiling (peak exposure)
 IDLH = immediately dangerous to life or health

ppm = parts per million in air
 mg/m³ = milligrams per cubic meter of air
 NE = not established
 NA = not applicable